

Technical Documentation

Dekorator Color Weekend Matt™

Colored interior paint for walls and ceilings

AREA OF APPLICATION:

Durable decorative coating for interior painting of walls and ceilings. Allows easy cleaning when dirty.

CLASSIFICATION:

- Water soluble product
- Binding agent polymer dispersion
- For interior use
- Color range: white and 25 finished colors

APPLICATION DESCRIPTION:

The paint should be thoroughly mixed before use. Apply to sound, well-cleaned surfaces. Priming with a suitable wall primer is recommended. Apply in **two coats** at intervals of about **3 hours** with a brush or a roller. For achieving the best results, it is advised that the temperature of the treated surface **does not exceed +35°C** and relative ambient **humidity of 60%.** Work at temperatures above **+10°C**. After finishing work, the tools should be cleaned immediately with water. The paint supplied is ready for use. If necessary, it can be diluted with water up to 5%.

- **Consumption:** 100-120 ml /m² for full coverage depending on color
- Drying: 3 hours at 23°C

STORAGE:

Shelf life 36 months from the date of manufacture, in factory sealed packaging. Store in dry and covered storage areas, protected from direct sunlight. Storage temperature of $+5^{\circ}C$ to $+35^{\circ}C$. Keep away from frost.

PACKAGING:

The paint is available in plastic packaging from 2.5L.

Note: For uniformity of the colour of the coating, one or more packages should be mixed before use



BUL. "LIPNIK" 123, 7005 EASTERN INDUSTRIAL ZONE, RUSE, BULGARIA



TECHNICAL DATA

Appearance after stirring:	Homogeneous dense mass
Content of non-volatile substances (105±2)°C/2h, in %:	57÷65
pH Value:	8÷9,5
Brookfield viscosity KU-2 at (23±0.5)°C, in KU:	100 ÷115
Density, in g/cm^3:	1,50÷1,65
Stability at (23±2) °C, up to grade 4, in h not more than:	3
Maximum VOC content for this product (Cat. A/a):	30 g/l
Color:	Spectrophotometric with total color difference $\Delta E \le 2$